

tf.errors.UnauthenticatedError

Contents

Class UnauthenticatedError

Properties

error_code

message

Class UnauthenticatedError

Inherits From: [OpError](#)

Defined in [tensorflow/python/framework/errors_impl.py](#).

See the guide: [Running Graphs > Error classes and convenience functions](#)

The request does not have valid authentication credentials.

This exception is not currently used.

Properties

error_code

The integer error code that describes the error.

message

The error message that describes the error.

node_def

The [NodeDef](#) proto representing the op that failed.

op

The operation that failed, if known.

N.B. If the failed op was synthesized at runtime, e.g. a [Send](#) or [Recv](#) op, there will be no corresponding [tf.Operation](#) object. In that case, this will return [None](#), and you should instead use the [tf.OpError.node_def](#) to discover information about the op.

Returns:

The [Operation](#) that failed, or None.

Methods

`__init__`

```
__init__(  
    node_def,  
    op,  
    message  
)
```

Creates an `UnauthenticatedError`.

Except as otherwise noted, the content of this page is licensed under the [Creative Commons Attribution 3.0 License](#), and code samples are licensed under the [Apache 2.0 License](#). For details, see our [Site Policies](#). Java is a registered trademark of Oracle and/or its affiliates.

Last updated November 2, 2017.

Stay Connected

[Blog](#)

[GitHub](#)

[Twitter](#)

Support

[Issue Tracker](#)

[Release Notes](#)

[Stack Overflow](#)

English

[Terms](#) | [Privacy](#)