TopogrElow

TensorFlow API r1.4

tf.keras.callbacks.Callback

```
Contents
Class Callback
Methods
__init__
on_batch_begin
```

Class Callback

Defined in tensorflow/python/keras/_impl/keras/callbacks.py.

Abstract base class used to build new callbacks.

Properties

```
params: dict. Training parameters
  (eg. verbosity, batch size, number of epochs...).
model: instance of `keras.models.Model`.
  Reference of the model being trained.
```

The **logs** dictionary that callback methods take as argument will contain keys for quantities relevant to the current batch or epoch.

Currently, the .fit() method of the Sequential model class will include the following quantities in the logs that it passes to its callbacks:

```
on_epoch_end: logs include `acc` and `loss`, and
  optionally include `val_loss`
  (if validation is enabled in `fit`), and `val_acc`
   (if validation and accuracy monitoring are enabled).
on_batch_begin: logs include `size`,
   the number of samples in the current batch.
on_batch_end: logs include `loss`, and optionally `acc`
  (if accuracy monitoring is enabled).
```

Methods

```
__init__
```

```
__init__()
```

on_batch_begin

```
on_batch_begin(
   batch,
   logs=None
)
```

on_batch_end

```
on_batch_end(
   batch,
   logs=None
)
```

on_epoch_begin

```
on_epoch_begin(
    epoch,
    logs=None
)
```

on_epoch_end

```
on_epoch_end(
    epoch,
    logs=None
)
```

on_train_begin

```
on_train_begin(logs=None)
```

on_train_end

```
on_train_end(logs=None)
```

set_model

```
set_model(model)
```

set_params

```
set_params(params)
```

Except as otherwise noted, the content of this page is licensed under the Creative Commons Attribution 3.0 License, and code samples are licensed under the Apache 2.0 License. For details, see our Site Policies. Java is a registered trademark of Oracle and/or its affiliates.

Last updated November 2, 2017.

Blog	
GitHub	
Twitter	
Support	
Issue Tracker	
Release Notes	
Stack Overflow	
English	
Terms Privacy	