TencorFlow

TensorFlow API r1.4

tf.contrib.data.read_batch_features

```
read_batch_features(
    file_pattern,
    batch_size,
    features,
    reader,
    reader_args=None,
    randomize_input=True,
    num_epochs=None,
    capacity=10000
)
```

Defined in tensorflow/contrib/data/python/ops/readers.py.

Reads batches of Examples.

Example:

```
serialized_examples = [
  features {
    feature { key: "age" value { int64_list { value: [ 0 ] } } }
    feature { key: "gender" value { bytes_list { value: [ "f" ] } } }
    feature { key: "kws" value { bytes_list { value: [ "code", "art" ] } } }
},
features {
    feature { key: "age" value { int64_list { value: [] } } }
    feature { key: "gender" value { bytes_list { value: [ "f" ] } } }
    feature { key: "kws" value { bytes_list { value: [ "sports" ] } } }
}
```

We can use arguments:

```
features: {
   "age": FixedLenFeature([], dtype=tf.int64, default_value=-1),
   "gender": FixedLenFeature([], dtype=tf.string),
   "kws": VarLenFeature(dtype=tf.string),
}
```

And the expected output is:

```
{
  "age": [[0], [-1]],
  "gender": [["f"], ["f"]],
  "kws": SparseTensor(
   indices=[[0, 0], [0, 1], [1, 0]],
   values=["code", "art", "sports"]
   dense_shape=[2, 2]),
}
```

Args:

• file_pattern: List of files or patterns of file paths containing Example records. See tf.gfile.Glob for pattern

rules.

- batch_size: An int representing the number of consecutive elements of this dataset to combine in a single batch.
- features: A dict mapping feature keys to FixedLenFeature or VarLenFeature values. See tf.parse_example.
- reader: A function or class that can be called with a **filenames** tensor and (optional) **reader_args** and returns a **Dataset** of serialized Examples.
- reader_args: Additional arguments to pass to the reader class.
- randomize_input: Whether the input should be randomized.
- num_epochs: Integer specifying the number of times to read through the dataset. If None, cycles through the dataset forever.
- capacity: Capacity of the ShuffleDataset. A large capacity ensures better shuffling but would increase memory
 usage and startup time.

Returns:

A dict from keys in features to Tensor or SparseTensor objects.

Except as otherwise noted, the content of this page is licensed under the Creative Commons Attribution 3.0 License, and code samples are licensed under the Apache 2.0 License. For details, see our Site Policies. Java is a registered trademark of Oracle and/or its affiliates.

Last updated November 2, 2017.

