

## Module: tf.metrics

[Contents](#)[Functions](#)

Defined in [tensorflow/python/ops/metrics.py](#).

Evaluation-related metrics.

## Functions

[accuracy\(...\)](#) : Calculates how often **predictions** matches **labels** .

[auc\(...\)](#) : Computes the approximate AUC via a Riemann sum.

[false\\_negatives\(...\)](#) : Computes the total number of false negatives.

[false\\_negatives\\_at\\_thresholds\(...\)](#) : Computes false negatives at provided threshold values.

[false\\_positives\(...\)](#) : Sum the weights of false positives.

[false\\_positives\\_at\\_thresholds\(...\)](#) : Computes false positives at provided threshold values.

[mean\(...\)](#) : Computes the (weighted) mean of the given values.

[mean\\_absolute\\_error\(...\)](#) : Computes the mean absolute error between the labels and predictions.

[mean\\_cosine\\_distance\(...\)](#) : Computes the cosine distance between the labels and predictions.

[mean\\_iou\(...\)](#) : Calculate per-step mean Intersection-Over-Union (mIOU).

[mean\\_per\\_class\\_accuracy\(...\)](#) : Calculates the mean of the per-class accuracies.

[mean\\_relative\\_error\(...\)](#) : Computes the mean relative error by normalizing with the given values.

[mean\\_squared\\_error\(...\)](#) : Computes the mean squared error between the labels and predictions.

[mean\\_tensor\(...\)](#) : Computes the element-wise (weighted) mean of the given tensors.

[percentage\\_below\(...\)](#) : Computes the percentage of values less than the given threshold.

[precision\(...\)](#) : Computes the precision of the predictions with respect to the labels.

[precision\\_at\\_thresholds\(...\)](#) : Computes precision values for different **thresholds** on **predictions** .

[recall\(...\)](#) : Computes the recall of the predictions with respect to the labels.

[recall\\_at\\_k\(...\)](#) : Computes recall@k of the predictions with respect to sparse labels.

[recall\\_at\\_thresholds\(...\)](#) : Computes various recall values for different **thresholds** on **predictions** .

[root\\_mean\\_squared\\_error\(...\)](#) : Computes the root mean squared error between the labels and predictions.

[sensitivity\\_at\\_specificity\(...\)](#) : Computes the specificity at a given sensitivity.

`sparse_average_precision_at_k(...)` : Computes average precision@k of predictions with respect to sparse labels.

`sparse_precision_at_k(...)` : Computes precision@k of the predictions with respect to sparse labels.

`specificity_at_sensitivity(...)` : Computes the specificity at a given sensitivity.

`true_negatives_at_thresholds(...)` : Computes true negatives at provided threshold values.

`true_positives(...)` : Sum the weights of true\_positives.

`true_positives_at_thresholds(...)` : Computes true positives at provided threshold values.

---

Except as otherwise noted, the content of this page is licensed under the [Creative Commons Attribution 3.0 License](#), and code samples are licensed under the [Apache 2.0 License](#). For details, see our [Site Policies](#). Java is a registered trademark of Oracle and/or its affiliates.

Last updated November 2, 2017.

## Stay Connected

[Blog](#)

[GitHub](#)

[Twitter](#)

## Support

[Issue Tracker](#)

[Release Notes](#)

[Stack Overflow](#)

English

[Terms](#) | [Privacy](#)