

## Module: tf.keras.callbacks

[Contents](#)[Classes](#)

Defined in [tensorflow/python/keras/callbacks/\\_\\_init\\_\\_.py](#).

Keras callback classes.

## Classes

**class** [BaseLogger](#) : Callback that accumulates epoch averages of metrics.

**class** [CSVLogger](#) : Callback that streams epoch results to a csv file.

**class** [Callback](#) : Abstract base class used to build new callbacks.

**class** [EarlyStopping](#) : Stop training when a monitored quantity has stopped improving.

**class** [History](#) : Callback that records events into a [History](#) object.

**class** [LambdaCallback](#) : Callback for creating simple, custom callbacks on-the-fly.

**class** [LearningRateScheduler](#) : Learning rate scheduler.

**class** [ModelCheckpoint](#) : Save the model after every epoch.

**class** [ProgbarLogger](#) : Callback that prints metrics to stdout.

**class** [ReduceLROnPlateau](#) : Reduce learning rate when a metric has stopped improving.

**class** [RemoteMonitor](#) : Callback used to stream events to a server.

**class** [TensorBoard](#) : Tensorboard basic visualizations.

**class** [TerminateOnNaN](#) : Callback that terminates training when a NaN loss is encountered.

Except as otherwise noted, the content of this page is licensed under the [Creative Commons Attribution 3.0 License](#), and code samples are licensed under the [Apache 2.0 License](#). For details, see our [Site Policies](#). Java is a registered trademark of Oracle and/or its affiliates.

Last updated November 2, 2017.

### Stay Connected

[Blog](#)[GitHub](#)[Twitter](#)

### Support

[Issue Tracker](#)

[Release Notes](#)

[Stack Overflow](#)

**English**

[Terms](#) | [Privacy](#)