TopoorFlow

TensorFlow API r1.4

tf.contrib.kfac.fisher_blocks.FisherBlock

```
Contents

Class FisherBlock

Methods
__init__
instantiate_factors
multiply
multiply_inverse
tensors_to_compute_grads
```

Class FisherBlock

Defined in tensorflow/contrib/kfac/python/ops/fisher_blocks.py.

Abstract base class for objects modeling approximate Fisher matrix blocks.

Subclasses must implement multiply_inverse(), instantiate_factors(), and tensors_to_compute_grads() methods.

Methods

```
__init__
```

```
__init__(layer_collection)
```

instantiate_factors

```
instantiate_factors(
   grads_list,
   damping
)
```

Creates and registers the component factors of this Fisher block.

Args:

- grads_list: A list gradients (each a Tensor or tuple of Tensors) with respect to the tensors returned by tensors_to_compute_grads() that are to be used to estimate the block.
- damping: The damping factor (float or Tensor).

multiply

```
multiply(vector)
```

Multiplies the vector by the (damped) block.

Args:

vector: The vector (a Tensor or tuple of Tensors) to be multiplied.

Returns:

The vector left-multiplied by the (damped) block.

multiply_inverse

```
multiply_inverse(vector)
```

Multiplies the vector by the (damped) inverse of the block.

Args:

vector: The vector (a Tensor or tuple of Tensors) to be multiplied.

Returns:

The vector left-multiplied by the (damped) inverse of the block.

tensors_to_compute_grads

tensors_to_compute_grads()

Returns the Tensor(s) with respect to which this FisherBlock needs grads.

Except as otherwise noted, the content of this page is licensed under the Creative Commons Attribution 3.0 License, and code samples are licensed under the Apache 2.0 License. For details, see our Site Policies. Java is a registered trademark of Oracle and/or its affiliates.

Last updated November 2, 2017.

