TopcorFlow

TensorFlow API r1.4

tf.contrib.estimator.binary_classification_head

```
binary_classification_head(
    weight_column=None,
    thresholds=None,
    label_vocabulary=None,
    name=None
)
```

Defined in tensorflow/contrib/estimator/python/estimator/head.py.

Creates a _Head for single label binary classification.

This head uses sigmoid_cross_entropy_with_logits loss.

This head expects to be fed float labels of shape (batch_size, 1).

Args:

- weight_column: A string or a _NumericColumn created by tf.feature_column.numeric_column defining feature column representing weights. It is used to down weight or boost examples during training. It will be multiplied by the loss of the example.
- thresholds: Iterable of floats in the range (0, 1). For binary classification metrics such as precision and recall, an eval metric is generated for each threshold value. This threshold is applied to the logistic values to determine the binary classification (i.e., above the threshold is true, below is false.
- label_vocabulary: A list of strings represents possible label values. If it is not given, that means labels are already encoded within [0, 1]. If given, labels must be string type and have any value in label_vocabulary. Also there will be errors if vocabulary is not provided and labels are string.
- name: name of the head. If provided, summary and metrics keys will be suffixed by "/" + name.

Returns:

An instance of **_Head** for binary classification.

Raises:

• ValueError: if thresholds contains a value outside of (0, 1).

Except as otherwise noted, the content of this page is licensed under the Creative Commons Attribution 3.0 License, and code samples are licensed under the Apache 2.0 License. For details, see our Site Policies. Java is a registered trademark of Oracle and/or its affiliates.

Last updated November 2, 2017.

Stay Connected

Blog

GitHub

Twitter			
Support			
Issue Tracker			
Release Notes			
Stack Overflow			
English			
Terms Privacy			