

tf.contrib.gan.losses.wargs.wasserstein_discriminator_loss

```
wasserstein_discriminator_loss(  
    discriminator_real_outputs,  
    discriminator_gen_outputs,  
    real_weights=1.0,  
    generated_weights=1.0,  
    scope=None,  
    loss_collection=tf.GraphKeys.LOSSES,  
    reduction=losses.Reduction.SUM_BY_NONZERO_WEIGHTS,  
    add_summaries=False  
)
```

Defined in [tensorflow/contrib/gan/python/losses/python/losses_impl.py](#).

Wasserstein discriminator loss for GANs.

See **Wasserstein GAN** (<https://arxiv.org/abs/1701.07875>) for more details.

Args:

- `discriminator_real_outputs`: Discriminator output on real data.
- `discriminator_gen_outputs`: Discriminator output on generated data. Expected to be in the range of $(-\infty, \infty)$.
- `real_weights`: Optional **Tensor** whose rank is either 0, or the same rank as `discriminator_real_outputs`, and must be broadcastable to `discriminator_real_outputs` (i.e., all dimensions must be either 1, or the same as the corresponding dimension).
- `generated_weights`: Same as `real_weights`, but for `discriminator_gen_outputs`.
- `scope`: The scope for the operations performed in computing the loss.
- `loss_collection`: collection to which this loss will be added.
- `reduction`: A **tf.losses.Reduction** to apply to loss.
- `add_summaries`: Whether or not to add summaries for the loss.

Returns:

A loss Tensor. The shape depends on `reduction`.

Except as otherwise noted, the content of this page is licensed under the [Creative Commons Attribution 3.0 License](#), and code samples are licensed under the [Apache 2.0 License](#). For details, see our [Site Policies](#). Java is a registered trademark of Oracle and/or its affiliates.

Last updated November 2, 2017.

Stay Connected

[Blog](#)

[GitHub](#)

[Twitter](#)

Support

[Issue Tracker](#)

[Release Notes](#)

[Stack Overflow](#)

English

[Terms](#) | [Privacy](#)