TopogrElow

TensorFlow API r1.4

tf.random_poisson

```
random_poisson(
   lam,
   shape,
   dtype=tf.float32,
   seed=None,
   name=None
)
```

Defined in tensorflow/python/ops/random_ops.py.

Draws shape samples from each of the given Poisson distribution(s).

lam is the rate parameter describing the distribution(s).

Example:

samples = tf.random_poisson([0.5, 1.5], [10]) # samples has shape [10, 2], where each slice [:, 0] and [:, 1] represents # the samples drawn from each distribution

samples = $tf.random_poisson([12.2, 3.3], [7, 5])$ # samples has shape [7, 5, 2], where each slice [:, :, 0] and [:, :, 1] # represents the 7x5 samples drawn from each of the two distributions

Args:

- lam: A Tensor or Python value or N-D array of type dtype. lam provides the rate parameter(s) describing the poisson distribution(s) to sample.
- shape: A 1-D integer Tensor or Python array. The shape of the output samples to be drawn per "rate"-parameterized distribution.
- dtype: The type of lam and the output: float16, float32, or float64.
- seed: A Python integer. Used to create a random seed for the distributions. See tf.set_random_seed for behavior.
- name: Optional name for the operation.

Returns:

samples: a Tensor of shape tf.concat(shape, tf.shape(lam)) with values of type dtype.

Except as otherwise noted, the content of this page is licensed under the Creative Commons Attribution 3.0 License, and code samples are licensed under the Apache 2.0 License. For details, see our Site Policies. Java is a registered trademark of Oracle and/or its affiliates.

Last updated November 2, 2017.

Stay Connected

Blog

GitHub

Twitter

Support Issue Tracker Release Notes Stack Overflow English Terms | Privacy