

tf.contrib.learn.SKCompat

Contents

Class SKCompat

Methods

`__init__``fit`Class **SKCompat**Defined in [tensorflow/contrib/learn/python/learn/estimators/estimator.py](#).

Scikit learn wrapper for TensorFlow Learn Estimator.

Methods

`__init__`

```
__init__(estimator)
```

`fit`

```
fit(  
    x,  
    y,  
    batch_size=128,  
    steps=None,  
    max_steps=None,  
    monitors=None  
)
```

`get_params`

```
get_params(deep=True)
```

Get parameters for this estimator.

Args:

- `deep` : boolean, optional

If `True`, will return the parameters for this estimator and contained subobjects that are estimators.

Returns:

- `params` : mapping of string to any Parameter names mapped to their values.

predict

```
predict(  
    x,  
    batch_size=128,  
    outputs=None  
)
```

score

```
score(  
    x,  
    y,  
    batch_size=128,  
    steps=None,  
    metrics=None,  
    name=None  
)
```

set_params

```
set_params(**params)
```

Set the parameters of this estimator.

The method works on simple estimators as well as on nested objects (such as pipelines). The former have parameters of the form `<component>__<parameter>` so that it's possible to update each component of a nested object.

Args:

- `**params` : Parameters.

Returns:

self

Raises:

- `ValueError` : If params contain invalid names.

Except as otherwise noted, the content of this page is licensed under the [Creative Commons Attribution 3.0 License](#), and code samples are licensed under the [Apache 2.0 License](#). For details, see our [Site Policies](#). Java is a registered trademark of Oracle and/or its affiliates.

Last updated November 2, 2017.

Stay Connected

Blog

GitHub

Twitter

Support

[Issue Tracker](#)

[Release Notes](#)

[Stack Overflow](#)

English

[Terms](#) | [Privacy](#)