

tf.random_uniform_initializer

Contents

Class `random_uniform_initializer`

Aliases:

Methods

`__init__`

`__call__`

`from_config`

`get_config`

Class `random_uniform_initializer`

Inherits From: [Initializer](#)

Aliases:

- Class `tf.initializers.random_uniform`
- Class `tf.keras.initializers.RandomUniform`
- Class `tf.random_uniform_initializer`

Defined in [tensorflow/python/ops/init_ops.py](#).

See the guide: [Variables > Sharing Variables](#)

Initializer that generates tensors with a uniform distribution.

Args:

- `minval`: A python scalar or a scalar tensor. Lower bound of the range of random values to generate.
- `maxval`: A python scalar or a scalar tensor. Upper bound of the range of random values to generate. Defaults to 1 for float types.
- `seed`: A Python integer. Used to create random seeds. See [tf.set_random_seed](#) for behavior.
- `dtype`: The data type.

Methods

`__init__`

```
__init__(  
    minval=0,  
    maxval=None,  
    seed=None,  
    dtype=tf.float32  
)
```

`__call__`

```
__call__(
    shape,
    dtype=None,
    partition_info=None
)
```

`from_config`

```
from_config(
    cls,
    config
)
```

Instantiates an initializer from a configuration dictionary.

Example:

```
initializer = RandomUniform(-1, 1)
config = initializer.get_config()
initializer = RandomUniform.from_config(config)
```

Args:

- `config`: A Python dictionary. It will typically be the output of `get_config`.

Returns:

An Initializer instance.

`get_config`

```
get_config()
```

Except as otherwise noted, the content of this page is licensed under the [Creative Commons Attribution 3.0 License](#), and code samples are licensed under the [Apache 2.0 License](#). For details, see our [Site Policies](#). Java is a registered trademark of Oracle and/or its affiliates.

Last updated November 2, 2017.

Stay Connected

[Blog](#)

[GitHub](#)

[Twitter](#)

Support

[Issue Tracker](#)

[Release Notes](#)

[Stack Overflow](#)

English

[Terms](#) | [Privacy](#)