

tf.contrib.learn.extract_dask_data

```
extract_dask_data(data)
```

Defined in [tensorflow/contrib/learn/python/learn/learn_io/dask_io.py](#).

See the guide: [Learn \(contrib\) > Input processing](#)

Extract data from `dask.Series` or `dask.DataFrame` for predictors.

Given a distributed `dask.DataFrame` or `dask.Series` containing columns or names for one or more predictors, this operation returns a single `dask.DataFrame` or `dask.Series` that can be iterated over.

Args:

- `data`: A distributed `dask.DataFrame` or `dask.Series`.

Returns:

A `dask.DataFrame` or `dask.Series` that can be iterated over. If the supplied argument is neither a `dask.DataFrame` nor a `dask.Series` this operation returns it without modification.

Except as otherwise noted, the content of this page is licensed under the [Creative Commons Attribution 3.0 License](#), and code samples are licensed under the [Apache 2.0 License](#). For details, see our [Site Policies](#). Java is a registered trademark of Oracle and/or its affiliates.

Last updated November 2, 2017.

Stay Connected[Blog](#)[GitHub](#)[Twitter](#)**Support**[Issue Tracker](#)[Release Notes](#)[Stack Overflow](#)[English](#)[Terms](#) | [Privacy](#)