

tf.contrib.learn.ExportStrategy

Contents

Class `ExportStrategy`

Properties

`export_fn`

`name`

Methods

`__new__`

`export`

Class `ExportStrategy`

Defined in [tensorflow/contrib/learn/python/learn/export_strategy.py](#).

See the guide: [Learn \(contrib\) > Distributed training utilities](#)

A class representing a type of model export.

Typically constructed by a utility function specific to the exporter, such as

`saved_model_export_utils.make_export_strategy()`.

The fields are:

- `name`: The directory name under the export base directory where exports of this type will be written.

- `export_fn`: A function that writes an export, given an estimator, a destination path, and optionally a checkpoint path and an evaluation result for that checkpoint. This `export_fn()` may be run repeatedly during continuous training, or just once at the end of fixed-length training. Note the `export_fn()` may choose whether or not to export based on the eval result or based on an internal timer or any other criterion, if exports are not desired for every checkpoint.

The signature of this function must be one of:

- `(estimator, export_path) -> export_path`
- `(estimator, export_path, checkpoint_path) -> export_path`
- `(estimator, export_path, checkpoint_path, eval_result) -> export_path`

Properties

`export_fn`

Alias for field number 1

`name`

Alias for field number 0

Methods

`__new__`

```
__new__(
    _cls,
    name,
    export_fn
)
```

Create new instance of ExportStrategy(name, export_fn)

export

```
export(
    estimator,
    export_path,
    checkpoint_path=None,
    eval_result=None
)
```

Exports the given Estimator to a specific format.

Args:

- `estimator` : the Estimator to export.
- `export_path` : A string containing a directory where to write the export.
- `checkpoint_path` : The checkpoint path to export. If None (the default), the strategy may locate a checkpoint (e.g. the most recent) by itself.
- `eval_result` : The output of Estimator.evaluate on this checkpoint. This should be set only if checkpoint_path is provided (otherwise it is unclear which checkpoint this eval refers to).

Returns:

The string path to the exported directory.

Raises:

- `ValueError` : if the export_fn does not have the required signature

Except as otherwise noted, the content of this page is licensed under the [Creative Commons Attribution 3.0 License](#), and code samples are licensed under the [Apache 2.0 License](#). For details, see our [Site Policies](#). Java is a registered trademark of Oracle and/or its affiliates.

Last updated November 2, 2017.

Stay Connected

[Blog](#)

[GitHub](#)

[Twitter](#)

Support

[Issue Tracker](#)

[Release Notes](#)

[Stack Overflow](#)

English

[Terms](#) | [Privacy](#)