TancarFlow

TensorFlow API r1.4

tf.contrib.metrics.streaming_false_positives

```
streaming_false_positives(
    predictions,
    labels,
    weights=None,
    metrics_collections=None,
    updates_collections=None,
    name=None
)
```

Defined in tensorflow/contrib/metrics/python/ops/metric_ops.py.

See the guide: Metrics (contrib) > Metric Ops

Sum the weights of false positives.

If weights is None, weights default to 1. Use weights of 0 to mask values.

Args:

- predictions: The predicted values, a Tensor of arbitrary dimensions. Will be cast to bool.
- labels: The ground truth values, a Tensor whose dimensions must match predictions. Will be cast to bool.
- weights: Optional **Tensor** whose rank is either 0, or the same rank as **labels**, and must be broadcastable to **labels** (i.e., all dimensions must be either **1**, or the same as the corresponding **labels** dimension).
- metrics_collections: An optional list of collections that the metric value variable should be added to.
- updates_collections: An optional list of collections that the metric update ops should be added to.
- name: An optional variable_scope name.

Returns:

- value_tensor: A Tensor representing the current value of the metric.
- update_op: An operation that accumulates the error from a batch of data.

Raises:

ValueError: If predictions and labels have mismatched shapes, or if weights is not None and its shape
doesn't match predictions, or if either metrics_collections or updates_collections are not a list or tuple.

Except as otherwise noted, the content of this page is licensed under the Creative Commons Attribution 3.0 License, and code samples are licensed under the Apache 2.0 License. For details, see our Site Policies. Java is a registered trademark of Oracle and/or its affiliates.

Last updated November 2, 2017.

GitHub	
Twitter	
Support	
Issue Tracker	
Release Notes	
Stack Overflow	
English	
Terms Privacy	