

## tf.keras.optimizers.Adagrad

## Contents

Class Adagrad

Methods

`__init__``from_config`Class **Adagrad**Inherits From: [Optimizer](#)Defined in [tensorflow/python/keras/\\_impl/keras/optimizers.py](#).

Adagrad optimizer.

It is recommended to leave the parameters of this optimizer at their default values.

## Arguments:

- `lr`: float >= 0. Learning rate.
- `epsilon`: float >= 0.
- `decay`: float >= 0. Learning rate decay over each update.

References: - [Adaptive Subgradient Methods for Online Learning and Stochastic Optimization](#)

## Methods

**`__init__`**

```
__init__(  
    lr=0.01,  
    epsilon=1e-08,  
    decay=0.0,  
    **kwargs  
)
```

**`from_config`**

```
from_config(  
    cls,  
    config  
)
```

**`get_config`**

```
get_config()
```

## get\_gradients

```
get_gradients(  
    loss,  
    params  
)
```

## get\_updates

```
get_updates(  
    loss,  
    params  
)
```

## get\_weights

```
get_weights()
```

Returns the current value of the weights of the optimizer.

Returns:

A list of numpy arrays.

## set\_weights

```
set_weights(weights)
```

Sets the weights of the optimizer, from Numpy arrays.

Should only be called after computing the gradients (otherwise the optimizer has no weights).

Arguments:

- **weights** : a list of Numpy arrays. The number of arrays and their shape must match number of the dimensions of the weights of the optimizer (i.e. it should match the output of **get\_weights**).

Raises:

- **ValueError** : in case of incompatible weight shapes.

---

Except as otherwise noted, the content of this page is licensed under the [Creative Commons Attribution 3.0 License](#), and code samples are licensed under the [Apache 2.0 License](#). For details, see our [Site Policies](#). Java is a registered trademark of Oracle and/or its affiliates.

Last updated November 2, 2017.

Stay Connected

Blog

[GitHub](#)

[Twitter](#)

**Support**

[Issue Tracker](#)

[Release Notes](#)

[Stack Overflow](#)

**English**

[Terms](#) | [Privacy](#)