

tf.self_adjoint_eigvals

Contents

Aliases:

Aliases:

- `tf.linalg.eigvalsh`
- `tf.self_adjoint_eigvals`

```
self_adjoint_eigvals(  
    tensor,  
    name=None  
)
```

Defined in `tensorflow/python/ops/linalg_ops.py`.

See the guide: [Math > Matrix Math Functions](#)

Computes the eigenvalues of one or more self-adjoint matrices.

★ **Note:** If your program backpropagates through this function, you should replace it with a call to `tf.self_adjoint_eig` (possibly ignoring the second output) to avoid computing the eigen decomposition twice. This is because the eigenvectors are used to compute the gradient w.r.t. the eigenvalues. See `_SelfAdjointEigV2Grad` in `linalg_grad.py`.

Args:

- `tensor`: `Tensor` of shape `[..., N, N]`.
- `name`: string, optional name of the operation.

Returns:

- `e`: Eigenvalues. Shape is `[..., N]`. The vector `e[..., :]` contains the `N` eigenvalues of `tensor[..., :, :]`.

Except as otherwise noted, the content of this page is licensed under the [Creative Commons Attribution 3.0 License](#), and code samples are licensed under the [Apache 2.0 License](#). For details, see our [Site Policies](#). Java is a registered trademark of Oracle and/or its affiliates.

Last updated November 2, 2017.

Stay Connected

[Blog](#)

[GitHub](#)

[Twitter](#)

Support

[Issue Tracker](#)

[Release Notes](#)

[Stack Overflow](#)

English

[Terms](#) | [Privacy](#)