

tf.igamma

```
igamma(  
    a,  
    x,  
    name=None  
)
```

Defined in `tensorflow/python/ops/gen_math_ops.py`.

See the guide: [Math > Basic Math Functions](#)

Compute the lower regularized incomplete Gamma function `Q(a, x)`.

The lower regularized incomplete Gamma function is defined as:

$$P(a, x) = \text{gamma}(a, x) / \text{Gamma}(a) = 1 - Q(a, x)$$

where

$$\text{gamma}(a, x) = \int_0^x t^{a-1} \exp(-t) dt$$

is the lower incomplete Gamma function.

Note, above `Q(a, x)` (`Igammac`) is the upper regularized complete Gamma function.

Args:

- `a`: A `Tensor`. Must be one of the following types: `float32`, `float64`.
- `x`: A `Tensor`. Must have the same type as `a`.
- `name`: A name for the operation (optional).

Returns:

A `Tensor`. Has the same type as `a`.

Except as otherwise noted, the content of this page is licensed under the [Creative Commons Attribution 3.0 License](#), and code samples are licensed under the [Apache 2.0 License](#). For details, see our [Site Policies](#). Java is a registered trademark of Oracle and/or its affiliates.

Last updated November 2, 2017.

Stay Connected

[Blog](#)

[GitHub](#)

[Twitter](#)

Support

[Issue Tracker](#)

[Release Notes](#)

[Stack Overflow](#)

English

[Terms](#) | [Privacy](#)