TancarFlow

TensorFlow API r1.4

tf.nn.quantized_relu_x

```
quantized_relu_x(
    features,
    max_value,
    min_features,
    max_features,
    out_type=tf.quint8,
    name=None
)
```

Defined in tensorflow/python/ops/gen_nn_ops.py.

See the guide: Neural Network > Candidate Sampling

Computes Quantized Rectified Linear X: min(max(features, 0), max_value)

Args:

- features: A Tensor. Must be one of the following types: qint8, quint8, qint16, quint16, qint32.
- max_value: A Tensor of type float32.
- min_features: A Tensor of type float32. The float value that the lowest quantized value represents.
- max_features: A Tensor of type float32. The float value that the highest quantized value represents.
- out_type: An optional tf.DType from: tf.qint8, tf.quint8, tf.quint16, tf.quint16, tf.quint32. Defaults to tf.quint8.
- name: A name for the operation (optional).

Returns:

A tuple of **Tensor** objects (activations, min_activations, max_activations).

- activations: A Tensor of type out_type. Has the same output shape as "features".
- min_activations: A Tensor of type float32. The float value that the lowest quantized value represents.
- max_activations: A Tensor of type float32. The float value that the highest quantized value represents.

Except as otherwise noted, the content of this page is licensed under the Creative Commons Attribution 3.0 License, and code samples are licensed under the Apache 2.0 License. For details, see our Site Policies. Java is a registered trademark of Oracle and/or its affiliates.

Last updated November 2, 2017.

Stay Connected

Blog

GitHub

Twitter

Support Issue Tracker Release Notes Stack Overflow English Terms | Privacy