tf.losses.absolute_difference

```
absolute_difference(
    labels,
    predictions,
    weights=1.0,
    scope=None,
    loss_collection=tf.GraphKeys.LOSSES,
    reduction=Reduction.SUM_BY_NONZERO_WEIGHTS
)
```

Defined in `tensorflow/python/ops/losses/losses_impl.py`.

Adds an Absolute Difference loss to the training procedure.

`weights` acts as a coefficient for the loss. If a scalar is provided, then the loss is simply scaled by the given value. If `weights` is a `Tensor` of shape `[batch_size]`, then the total loss for each sample of the batch is rescaled by the corresponding element in the `weights` vector. If the shape of `weights` matches the shape of `predictions`, then the loss of each measurable element of `predictions` is scaled by the corresponding value of `weights`.

Args:

- `labels` : The ground truth output tensor, same dimensions as 'predictions'.
- `predictions` : The predicted outputs.
- `weights` : Optional `Tensor` whose rank is either 0, or the same rank as `labels`, and must be broadcastable to `labels` (i.e., all dimensions must be either `1`, or the same as the corresponding `losses` dimension).
- `scope` : The scope for the operations performed in computing the loss.
- `loss_collection` : collection to which this loss will be added.
- `reduction` : Type of reduction to apply to loss.

Returns:

Weighted loss float `Tensor`. If `reduction` is `NONE`, this has the same shape as `labels`; otherwise, it is scalar.

Raises:

- `ValueError` : If the shape of `predictions` doesn't match that of `labels` or if the shape of `weights` is invalid or if `labels` or `predictions` is None.

Last updated November 2, 2017.

Stay Connected

Blog

GitHub

Twitter

Support

Issue Tracker

Release Notes

Stack Overflow

English

Terms | Privacy