## TopogrElow

TensorFlow API r1.4

tf.contrib.distributions.assign\_log\_moving\_mean\_exp

```
assign_log_moving_mean_exp(
    log_mean_exp_var,
    log_value,
    decay,
    name=None
)
```

Defined in tensorflow/contrib/distributions/python/ops/moving\_stats.py.

Compute the log of the exponentially weighted moving mean of the exp.

If log\_value is a draw from a stationary random variable, this function approximates log(E[exp(log\_value)]), i.e., a weighted log-sum-exp. More precisely, a tf.Variable, log\_mean\_exp\_var, is updated by log\_value using the following identity:

In addition to numerical stability, this formulation is advantageous because **log\_mean\_exp\_var** can be updated in a lock-free manner, i.e., using **assign\_add**. (Note: the updates are not thread-safe; it's just that the update to the tf. Variable is presumed efficient due to being lock-free.)

## Args:

- log\_mean\_exp\_var: float -like Variable representing the log of the exponentially weighted moving mean of the exp. Same shape as log\_value.
- log\_value: float-like Tensor representing a new (streaming) observation. Same shape as log\_mean\_exp\_var.
- decay: A float-like Tensor. The moving mean decay. Typically close to 1., e.g., 0.999.
- name: Optional name of the returned operation.

## Returns:

• log\_mean\_exp\_var: A reference to the input 'Variable' tensor with the log\_value -updated log of the exponentially weighted moving mean of exp.

## Raises:

- TypeError: if log\_mean\_exp\_var does not have float type dtype.
- TypeError: if log\_mean\_exp\_var, log\_value, decay have different base\_dtype.

Except as otherwise noted, the content of this page is licensed under the Creative Commons Attribution 3.0 License, and code samples are licensed under the Apache 2.0 License. For details, see our Site Policies. Java is a registered trademark of Oracle and/or its affiliates.

Last updated November 2, 2017.

