

tf.segment_min

```
segment_min(
    data,
    segment_ids,
    name=None
)
```

Defined in `tensorflow/python/ops/gen_math_ops.py`.

See the guide: [Math > Segmentation](#)

Computes the minimum along segments of a tensor.


Read [the section on segmentation](#) for an explanation of segments.

Computes a tensor such that $output_i = \min_j$ where \min is over j such that `segment_ids[j] == i`.

If the min is empty for a given segment ID i , `output[i] = 0`.

segment_ids

data



Args:

- `data`: A `Tensor`. Must be one of the following types: `float32`, `float64`, `int32`, `int64`, `uint8`, `int16`, `int8`, `uint16`, `half`.
- `segment_ids`: A `Tensor`. Must be one of the following types: `int32`, `int64`. A 1-D tensor whose rank is equal to the rank of `data`'s first dimension. Values should be sorted and can be repeated.
- `name`: A name for the operation (optional).

Returns:

A `Tensor`. Has the same type as `data`. Has same shape as data, except for dimension 0 which has size `k`, the number of segments.

Except as otherwise noted, the content of this page is licensed under the [Creative Commons Attribution 3.0 License](#), and code samples are licensed under the [Apache 2.0 License](#). For details, see our [Site Policies](#). Java is a registered trademark of Oracle and/or its affiliates.

Last updated November 2, 2017.

[Blog](#)

[GitHub](#)

[Twitter](#)

Support

[Issue Tracker](#)

[Release Notes](#)

[Stack Overflow](#)

English

Processing math: 0%