

tf.contrib.framework.deprecated_arg_values

```
deprecated_arg_values(  
    date,  
    instructions,  
    warn_once=True,  
    **deprecated_kwargs  
)
```

Defined in [tensorflow/python/util/deprecation.py](#).

See the guide: [Framework \(contrib\) > Deprecation](#)

Decorator for marking specific function argument values as deprecated.

This decorator logs a deprecation warning whenever the decorated function is called with the deprecated argument values. It has the following format:

Calling (from) with = is deprecated and will be removed after . Instructions for updating:

If **date** is None, 'after ' is replaced with 'in a future version'. will include the class name if it is a method.

It also edits the docstring of the function: ' (deprecated arguments)' is appended to the first line of the docstring and a deprecation notice is prepended to the rest of the docstring.

Args:

- **date** : String or None. The date the function is scheduled to be removed. Must be ISO 8601 (YYYY-MM-DD), or None
- **instructions** : String. Instructions on how to update code using the deprecated function.
- **warn_once** : If **True** , warn only the first time this function is called with deprecated argument values. Otherwise, every call (with a deprecated argument value) will log a warning.
- ****deprecated_kwargs** : The deprecated argument values.

Returns:

Decorated function or method.

Raises:

- **ValueError** : If date is not None or in ISO 8601 format, or instructions are empty.

Except as otherwise noted, the content of this page is licensed under the [Creative Commons Attribution 3.0 License](#), and code samples are licensed under the [Apache 2.0 License](#). For details, see our [Site Policies](#). Java is a registered trademark of Oracle and/or its affiliates.

Last updated November 2, 2017.

[Blog](#)

[GitHub](#)

[Twitter](#)

Support

[Issue Tracker](#)

[Release Notes](#)

[Stack Overflow](#)

English

[Terms](#) | [Privacy](#)