

# tf.floormod

## Contents

## Aliases:

## Aliases:

- `tf.floormod`
- `tf.mod`

```
floormod(  
    x,  
    y,  
    name=None  
)
```

Defined in `tensorflow/python/ops/gen_math_ops.py`.

See the guide: [Math > Arithmetic Operators](#)

Returns element-wise remainder of division. When `x < 0` xor `y < 0` is

true, this follows Python semantics in that the result here is consistent with a flooring divide. E.g. `floor(x / y) * y + mod(x, y) = x`.

**NOTE:** `FloorMod` supports broadcasting. More about broadcasting [here](#)

## Args:

- `x`: A `Tensor`. Must be one of the following types: `int32`, `int64`, `float32`, `float64`.
- `y`: A `Tensor`. Must have the same type as `x`.
- `name`: A name for the operation (optional).

## Returns:

A `Tensor`. Has the same type as `x`.

Except as otherwise noted, the content of this page is licensed under the [Creative Commons Attribution 3.0 License](#), and code samples are licensed under the [Apache 2.0 License](#). For details, see our [Site Policies](#). Java is a registered trademark of Oracle and/or its affiliates.

Last updated November 2, 2017.

## Stay Connected

[Blog](#)

[GitHub](#)

[Twitter](#)

Support

[Issue Tracker](#)

[Release Notes](#)

[Stack Overflow](#)

English

[Terms](#) | [Privacy](#)