TensorFlow

TensorFlow API r1.4

tf.contrib.image.transform

```
transform(
   images,
   transforms,
   interpolation='NEAREST'
)
```

Defined in tensorflow/contrib/image/python/ops/image_ops.py.

Applies the given transform(s) to the image(s).

Args:

- images: A tensor of shape (num_images, num_rows, num_columns, num_channels) (NHWC), (num_rows, num_columns, num_channels) (HWC), or (num_rows, num_columns) (HW).
- transforms: Projective transform matrix/matrices. A vector of length 8 or tensor of size N x 8. If one row of transforms is [a0, a1, a2, b0, b1, b2, c0, c1], then it maps the *output* point (x, y) to a transformed *input* point (x', y') = ((a0 x + a1 y + a2) / k, (b0 x + b1 y + b2) / k), where k = c0 x + c1 y + 1. The transforms are *inverted* compared to the transform mapping input points to output points.
- interpolation: Interpolation mode. Supported values: "NEAREST", "BILINEAR".

Returns:

Image(s) with the same type and shape as **images**, with the given transform(s) applied. Transformed coordinates outside of the input image will be filled with zeros.

Raises:

• TypeError: If image is an invalid type.

Except as otherwise noted, the content of this page is licensed under the Creative Commons Attribution 3.0 License, and code samples are licensed under the Apache 2.0 License. For details, see our Site Policies. Java is a registered trademark of Oracle and/or its affiliates.

Last updated November 2, 2017.

Stay Connected Blog GitHub Twitter Support Issue Tracker Release Notes

Stack Overflow

English

Terms | Privacy