

tf.keras.backend.conv2d

```
conv2d(  
    x,  
    kernel,  
    strides=(1, 1),  
    padding='valid',  
    data_format=None,  
    dilation_rate=(1, 1)  
)
```

Defined in [tensorflow/python/keras/_impl/keras/backend.py](#).

2D convolution.

Arguments:

- `x`: Tensor or variable.
- `kernel`: kernel tensor.
- `strides`: strides tuple.
- `padding`: string, `"same"` or `"valid"`.
- `data_format`: `"channels_last"` or `"channels_first"`. Whether to use Theano or TensorFlow data format for inputs/kernels/outputs.
- `dilation_rate`: tuple of 2 integers.

Returns:

A tensor, result of 2D convolution.

Raises:

- `ValueError`: if `data_format` is neither `channels_last` or `channels_first`.

Except as otherwise noted, the content of this page is licensed under the [Creative Commons Attribution 3.0 License](#), and code samples are licensed under the [Apache 2.0 License](#). For details, see our [Site Policies](#). Java is a registered trademark of Oracle and/or its affiliates.

Last updated November 2, 2017.

Stay Connected

[Blog](#)

[GitHub](#)

[Twitter](#)

[Support](#)

[Issue Tracker](#)

[Release Notes](#)

[Stack Overflow](#)

English

[Terms](#) | [Privacy](#)