

## tf.train.exponential\_decay

```
exponential_decay(  
    learning_rate,  
    global_step,  
    decay_steps,  
    decay_rate,  
    staircase=False,  
    name=None  
)
```

Defined in [tensorflow/python/training/learning\\_rate\\_decay.py](#).

See the guide: [Training > Decaying the learning rate](#)

Applies exponential decay to the learning rate.

When training a model, it is often recommended to lower the learning rate as the training progresses. This function applies an exponential decay function to a provided initial learning rate. It requires a **global\_step** value to compute the decayed learning rate. You can just pass a TensorFlow variable that you increment at each training step.

The function returns the decayed learning rate. It is computed as:

```
decayed_learning_rate = learning_rate *  
                        decay_rate ^ (global_step / decay_steps)
```

If the argument **staircase** is **True**, then **global\_step / decay\_steps** is an integer division and the decayed learning rate follows a staircase function.

Example: decay every 100000 steps with a base of 0.96:

```
...  
global_step = tf.Variable(0, trainable=False)  
starter_learning_rate = 0.1  
learning_rate = tf.train.exponential_decay(starter_learning_rate, global_step,  
                                           100000, 0.96, staircase=True)  
# Passing global_step to minimize() will increment it at each step.  
learning_step = (  
    tf.train.GradientDescentOptimizer(learning_rate)  
    .minimize(...my loss..., global_step=global_step)  
)
```

### Args:

- **learning\_rate**: A scalar **float32** or **float64 Tensor** or a Python number. The initial learning rate.
- **global\_step**: A scalar **int32** or **int64 Tensor** or a Python number. Global step to use for the decay computation. Must not be negative.
- **decay\_steps**: A scalar **int32** or **int64 Tensor** or a Python number. Must be positive. See the decay computation above.
- **decay\_rate**: A scalar **float32** or **float64 Tensor** or a Python number. The decay rate.
- **staircase**: Boolean. If **True** decay the learning rate at discrete intervals

- `name` : String. Optional name of the operation. Defaults to 'ExponentialDecay'.

Returns:

A scalar `Tensor` of the same type as `learning_rate`. The decayed learning rate.

Raises:

- `ValueError` : if `global_step` is not supplied.

---

Except as otherwise noted, the content of this page is licensed under the [Creative Commons Attribution 3.0 License](#), and code samples are licensed under the [Apache 2.0 License](#). For details, see our [Site Policies](#). Java is a registered trademark of Oracle and/or its affiliates.

Last updated November 2, 2017.

### Stay Connected

[Blog](#)

[GitHub](#)

[Twitter](#)

### Support

[Issue Tracker](#)

[Release Notes](#)

[Stack Overflow](#)

English

[Terms](#) | [Privacy](#)