

tf.diag

```
diag(  
    diagonal,  
    name=None  
)
```

Defined in `tensorflow/python/ops/gen_array_ops.py`.

See the guide: [Math > Matrix Math Functions](#)

Returns a diagonal tensor with a given diagonal values.

Given a `diagonal`, this operation returns a tensor with the `diagonal` and everything else padded with zeros. The diagonal is computed as follows:

Assume `diagonal` has dimensions $[D_1, \dots, D_k]$, then the output is a tensor of rank $2k$ with dimensions $[D_1, \dots, D_k, D_1, \dots, D_k]$ where:

`output[i1, ..., ik, i1, ..., ik] = diagonal[i1, ..., ik]` and 0 everywhere else.

For example:

```
# 'diagonal' is [1, 2, 3, 4]  
tf.diag(diagonal) ==> [[1, 0, 0, 0]  
                        [0, 2, 0, 0]  
                        [0, 0, 3, 0]  
                        [0, 0, 0, 4]]
```

Args:

- `diagonal`: A `Tensor`. Must be one of the following types: `float32`, `float64`, `int32`, `int64`, `complex64`, `complex128`. Rank k tensor where k is at most 3.
- `name`: A name for the operation (optional).

Returns:

A `Tensor`. Has the same type as `diagonal`.

Except as otherwise noted, the content of this page is licensed under the [Creative Commons Attribution 3.0 License](#), and code samples are licensed under the [Apache 2.0 License](#). For details, see our [Site Policies](#). Java is a registered trademark of Oracle and/or its affiliates.

Last updated November 2, 2017.

Stay Connected

[Blog](#)

[GitHub](#)

[Twitter](#)

Support

[Issue Tracker](#)

[Release Notes](#)

[Stack Overflow](#)

English

[Terms](#) | [Privacy](#)