

tf.train.add_queue_runner

Contents

Aliases:

Aliases:

- `tf.train.add_queue_runner`
- `tf.train.queue_runner.add_queue_runner`

```
add_queue_runner(  
    qr,  
    collection=tf.GraphKeys.QUEUE_RUNNERS  
)
```

Defined in [tensorflow/python/training/queue_runner_impl.py](#).

See the guides: [Reading data > Reading from files](#), [Training > Coordinator and QueueRunner](#)

Adds a `QueueRunner` to a collection in the graph.

When building a complex model that uses many queues it is often difficult to gather all the queue runners that need to be run. This convenience function allows you to add a queue runner to a well known collection in the graph.

The companion method `start_queue_runners()` can be used to start threads for all the collected queue runners.

Args:

- `qr`: A `QueueRunner`.
- `collection`: A `GraphKey` specifying the graph collection to add the queue runner to. Defaults to `GraphKeys.QUEUE_RUNNERS`.

Except as otherwise noted, the content of this page is licensed under the [Creative Commons Attribution 3.0 License](#), and code samples are licensed under the [Apache 2.0 License](#). For details, see our [Site Policies](#). Java is a registered trademark of Oracle and/or its affiliates.

Last updated November 2, 2017.

Stay Connected

[Blog](#)

[GitHub](#)

[Twitter](#)

Support

[Issue Tracker](#)

[Release Notes](#)

English

[Terms](#) | [Privacy](#)