

Module: `tf.contrib.crf`

Contents

Classes

Functions

Defined in `tensorflow/contrib/crf/__init__.py`.

Linear-chain CRF layer.

See the [CRF \(contrib\)](#) guide.

Classes

`class CrfDecodeBackwardRnnCell` : Computes backward decoding in a linear-chain CRF.

`class CrfDecodeForwardRnnCell` : Computes the forward decoding in a linear-chain CRF.

`class CrfForwardRnnCell` : Computes the alpha values in a linear-chain CRF.

Functions

`crf_binary_score(...)` : Computes the binary scores of tag sequences.

`crf_decode(...)` : Decode the highest scoring sequence of tags in TensorFlow.

`crf_log_likelihood(...)` : Computes the log-likelihood of tag sequences in a CRF.

`crf_log_norm(...)` : Computes the normalization for a CRF.

`crf_sequence_score(...)` : Computes the unnormalized score for a tag sequence.

`crf_unary_score(...)` : Computes the unary scores of tag sequences.

`viterbi_decode(...)` : Decode the highest scoring sequence of tags outside of TensorFlow.

Except as otherwise noted, the content of this page is licensed under the [Creative Commons Attribution 3.0 License](#), and code samples are licensed under the [Apache 2.0 License](#). For details, see our [Site Policies](#). Java is a registered trademark of Oracle and/or its affiliates.

Last updated November 2, 2017.

Stay Connected

[Blog](#)

[GitHub](#)

[Twitter](#)

Support

[Issue Tracker](#)

[Release Notes](#)

[Stack Overflow](#)

English

[Terms](#) | [Privacy](#)