

tf.contrib.seq2seq.BahdanauMonotonicAttention

Contents

Class BahdanauMonotonicAttention

Properties

alignments_size

batch_size

Class **BahdanauMonotonicAttention**Defined in [tensorflow/contrib/seq2seq/python/ops/attention_wrapper.py](#).

Monotonic attention mechanism with Bahadanau-style energy function.

This type of attention enforces a monotonic constraint on the attention distributions; that is once the model attends to a given point in the memory it can't attend to any prior points at subsequence output timesteps. It achieves this by using the `_monotonic_probability_fn` instead of softmax to construct its attention distributions. Since the attention scores are passed through a sigmoid, a learnable scalar bias parameter is applied after the score function and before the sigmoid. Otherwise, it is equivalent to BahdanauAttention. This approach is proposed in

Colin Raffel, Minh-Thang Luong, Peter J. Liu, Ron J. Weiss, Douglas Eck, "Online and Linear-Time Attention by Enforcing Monotonic Alignments." ICML 2017. <https://arxiv.org/abs/1704.00784>

Properties

alignments_size**batch_size****keys****memory_layer****query_layer****values**

Methods

__init__

```

__init__(
    num_units,
    memory,
    memory_sequence_length=None,
    normalize=False,
    score_mask_value=float('-inf'),
    sigmoid_noise=0.0,
    sigmoid_noise_seed=None,
    score_bias_init=0.0,
    mode='parallel',
    name='BahdanauMonotonicAttention'
)

```

Construct the Attention mechanism.

Args:

- `num_units` : The depth of the query mechanism.
- `memory` : The memory to query; usually the output of an RNN encoder. This tensor should be shaped `[batch_size, max_time, ...]`. `memory_sequence_length` (optional): Sequence lengths for the batch entries in memory. If provided, the memory tensor rows are masked with zeros for values past the respective sequence lengths.
- `normalize` : Python boolean. Whether to normalize the energy term.
- `score_mask_value` : (optional): The mask value for score before passing into `probability_fn`. The default is -inf. Only used if `memory_sequence_length` is not None.
- `sigmoid_noise` : Standard deviation of pre-sigmoid noise. See the docstring for `_monotonic_probability_fn` for more information.
- `sigmoid_noise_seed` : (optional) Random seed for pre-sigmoid noise.
- `score_bias_init` : Initial value for score bias scalar. It's recommended to initialize this to a negative value when the length of the memory is large.
- `mode` : How to compute the attention distribution. Must be one of 'recursive', 'parallel', or 'hard'. See the docstring for `tf.contrib.seq2seq.monotonic_attention` for more information.
- `name` : Name to use when creating ops.

`__call__`

```

__call__(
    query,
    previous_alignments
)

```

Score the query based on the keys and values.

Args:

- `query` : Tensor of dtype matching `self.values` and shape `[batch_size, query_depth]`.
- `previous_alignments` : Tensor of dtype matching `self.values` and shape `[batch_size, alignments_size]` (`alignments_size` is memory's `max_time`).

Returns:

- `alignments` : Tensor of dtype matching `self.values` and shape `[batch_size, alignments_size]` (`alignments_size` is memory's `max_time`).

initial_alignments

```
initial_alignments(  
    batch_size,  
    dtype  
)
```

Creates the initial alignment values for the monotonic attentions.

Initializes to dirac distributions, i.e. [1, 0, 0, ...memory length..., 0] for all entries in the batch.

Args:

- `batch_size`: `int32` scalar, the batch_size.
- `dtype`: The `dtype`.

Returns:

A `dtype` tensor shaped `[batch_size, alignments_size]` (`alignments_size` is the values' `max_time`).

Except as otherwise noted, the content of this page is licensed under the [Creative Commons Attribution 3.0 License](#), and code samples are licensed under the [Apache 2.0 License](#). For details, see our [Site Policies](#). Java is a registered trademark of Oracle and/or its affiliates.

Last updated November 2, 2017.

Stay Connected

[Blog](#)

[GitHub](#)

[Twitter](#)

Support

[Issue Tracker](#)

[Release Notes](#)

[Stack Overflow](#)

English

[Terms](#) | [Privacy](#)