

tf.self_adjoint_eig

Contents

Aliases:

Aliases:

- `tf.linalg.eigh`
- `tf.self_adjoint_eig`

```
self_adjoint_eig(  
    tensor,  
    name=None  
)
```

Defined in `tensorflow/python/ops/linalg_ops.py`.

See the guide: [Math > Matrix Math Functions](#)

Computes the eigen decomposition of a batch of self-adjoint matrices.

Computes the eigenvalues and eigenvectors of the innermost N-by-N matrices in `tensor` such that `tensor[..., :, :] * v[..., :, i] = e[..., i] * v[..., :, i]`, for $i=0 \dots N-1$.

Args:

- `tensor`: `Tensor` of shape `[..., N, N]`. Only the lower triangular part of each inner inner matrix is referenced.
- `name`: string, optional name of the operation.

Returns:

- `e`: Eigenvalues. Shape is `[..., N]`.
- `v`: Eigenvectors. Shape is `[..., N, N]`. The columns of the inner most matrices contain eigenvectors of the corresponding matrices in `tensor`

Except as otherwise noted, the content of this page is licensed under the [Creative Commons Attribution 3.0 License](#), and code samples are licensed under the [Apache 2.0 License](#). For details, see our [Site Policies](#). Java is a registered trademark of Oracle and/or its affiliates.

Last updated November 2, 2017.

Stay Connected

[Blog](#)

[GitHub](#)

[Twitter](#)

Support

[Issue Tracker](#)

[Release Notes](#)

[Stack Overflow](#)

English

[Terms](#) | [Privacy](#)