#### TancarFlow

TensorFlow API r1.4

# tf.sparse\_reduce\_max\_sparse

```
sparse_reduce_max_sparse(
    sp_input,
    axis=None,
    keep_dims=False,
    reduction_axes=None
)
```

Defined in tensorflow/python/ops/sparse\_ops.py.

Computes the max of elements across dimensions of a SparseTensor.

This Op takes a SparseTensor and is the sparse counterpart to **tf.reduce\_max()**. In contrast to SparseReduceSum, this Op returns a SparseTensor.

Reduces **sp\_input** along the dimensions given in **reduction\_axes**. Unless **keep\_dims** is true, the rank of the tensor is reduced by 1 for each entry in **reduction\_axes**. If **keep\_dims** is true, the reduced dimensions are retained with length 1.

If **reduction\_axes** has no entries, all dimensions are reduced, and a tensor with a single element is returned. Additionally, the axes can be negative, which are interpreted according to the indexing rules in Python.

### Args:

- sp\_input: The SparseTensor to reduce. Should have numeric type.
- axis: The dimensions to reduce; list or scalar. If None (the default), reduces all dimensions.
- keep\_dims: If true, retain reduced dimensions with length 1.
- reduction\_axes: Deprecated name of axis

## Returns:

The reduced SparseTensor.

Except as otherwise noted, the content of this page is licensed under the Creative Commons Attribution 3.0 License, and code samples are licensed under the Apache 2.0 License. For details, see our Site Policies. Java is a registered trademark of Oracle and/or its affiliates.

Last updated November 2, 2017.

# **Stay Connected** Blog

Diog

GitHub

Twitter

### Support

Issue Tracker

Release Notes
Stack Overflow

English
Terms | Privacy