TencorFlow

TensorFlow API r1.4

tf.contrib.bayesflow.csiszar_divergence.log1p_abs

```
log1p_abs(
    logu,
    name=None
)
```

Defined in tensorflow/contrib/bayesflow/python/ops/csiszar_divergence_impl.py.

The log1p-abs Csiszar-function in log-space.

A Csiszar-function is a member of,

```
F = \{ f:R_+ \text{ to } R : f \text{ convex } \}.
```

The Log1p-Abs Csiszar-function is:

```
f(u) = u**(sign(u-1)) - 1
```

This function is so-named because it was invented from the following recipe. Choose a convex function g such that g(0)=0 and solve for f:

```
log(1 + f(u)) = g(log(u)).
<=>
f(u) = exp(g(log(u))) - 1
```

That is, the graph is identically **g** when y-axis is **log1p** -domain and x-axis is **log** -domain.

A

Warning: this function makes non-log-space calculations and may therefore be numerically unstable for |logu| >> 0.

Args:

- logu: float -like Tensor representing log(u) from above.
- name: Python str name prefixed to Ops created by this function.

Returns:

log1p_abs_of_u: float -like Tensor of the Csiszar-function evaluated at u = exp(logu).

Except as otherwise noted, the content of this page is licensed under the Creative Commons Attribution 3.0 License, and code samples are licensed under the Apache 2.0 License. For details, see our Site Policies. Java is a registered trademark of Oracle and/or its affiliates.

Last updated November 2, 2017.

Stay Connected

Blog

GitHub