TopogrElow

TensorFlow API r1.4

tf.contrib.seq2seq.BasicDecoder

Contents
Class BasicDecoder
Properties
batch_size
output_dtype

Class BasicDecoder

Inherits From: Decoder

Defined in tensorflow/contrib/seq2seq/python/ops/basic_decoder.py.

See the guide: Seq2seq Library (contrib) > Dynamic Decoding

Basic sampling decoder.

Properties

batch_size

output_dtype

output_size

Methods

__init__

```
__init__(
    cell,
    helper,
    initial_state,
    output_layer=None
)
```

Initialize BasicDecoder.

Args:

- cell: An RNNCell instance.
- helper: A Helper instance.
- initial_state: A (possibly nested tuple of...) tensors and TensorArrays. The initial state of the RNNCell.
- output_layer: (Optional) An instance of tf.layers.Layer, i.e., tf.layers.Dense. Optional layer to apply to the

RNN output prior to storing the result or sampling.

Raises:

• TypeError: if cell, helper or output_layer have an incorrect type.

finalize

```
finalize(
   outputs,
   final_state,
   sequence_lengths
)
```

initialize

```
initialize(name=None)
```

Initialize the decoder.

Args:

• name: Name scope for any created operations.

Returns:

```
(finished, first_inputs, initial_state).
```

step

```
step(
    time,
    inputs,
    state,
    name=None
)
```

Perform a decoding step.

Args:

- time: scalar int32 tensor.
- inputs: A (structure of) input tensors.
- state: A (structure of) state tensors and TensorArrays.
- name: Name scope for any created operations.

Returns:

```
(outputs, next_state, next_inputs, finished).
```

Except as otherwise noted, the content of this page is licensed under the Creative Commons Attribution 3.0 License, and code samples are licensed under the Apache 2.0 License. For details, see our Site Policies. Java is a registered trademark of Oracle and/or its affiliates.

Last updated November 2, 2017.

