

## tf.contrib.training.StopAfterNEvalsHook

### Contents

Class `StopAfterNEvalsHook`

### Methods

`__init__`

`after_create_session`

## Class `StopAfterNEvalsHook`

Inherits From: `SessionRunHook`

Defined in `tensorflow/python/training/evaluation.py`.

Run hook used by the evaluation routines to run the `eval_ops` N times.

## Methods

### `__init__`

```
__init__(  
    num_evals,  
    log_progress=True  
)
```

Constructs the run hook.

Args:

- `num_evals`: The number of evaluations to run for. if set to None, will iterate the dataset until all inputs are exhausted.
- `log_progress`: Whether to log evaluation progress, defaults to True.

### `after_create_session`

```
after_create_session(  
    session,  
    coord  
)
```

Called when new TensorFlow session is created.

This is called to signal the hooks that a new session has been created. This has two essential differences with the situation in which `begin` is called:

- When this is called, the graph is finalized and ops can no longer be added to the graph.
- This method will also be called as a result of recovering a wrapped session, not only at the beginning of the overall

session.

Args:

- `session`: A TensorFlow Session that has been created.
- `coord`: A Coordinator object which keeps track of all threads.

## after\_run

```
after_run(  
    run_context,  
    run_values  
)
```

## before\_run

```
before_run(run_context)
```

## begin

```
begin()
```

Called once before using the session.

When called, the default graph is the one that will be launched in the session. The hook can modify the graph by adding new operations to it. After the `begin()` call the graph will be finalized and the other callbacks can not modify the graph anymore. Second call of `begin()` on the same graph, should not change the graph.

## end

```
end(session)
```

Called at the end of session.

The `session` argument can be used in case the hook wants to run final ops, such as saving a last checkpoint.

If `session.run()` raises exception other than `OutOfRangeError` or `StopIteration` then `end()` is not called. Note the difference between `end()` and `after_run()` behavior when `session.run()` raises `OutOfRangeError` or `StopIteration`. In that case `end()` is called but `after_run()` is not called.

Args:

- `session`: A TensorFlow Session that will be soon closed.

---

Except as otherwise noted, the content of this page is licensed under the [Creative Commons Attribution 3.0 License](#), and code samples are licensed under the [Apache 2.0 License](#). For details, see our [Site Policies](#). Java is a registered trademark of Oracle and/or its affiliates.

Last updated November 2, 2017.

[Blog](#)

[GitHub](#)

[Twitter](#)

**Support**

[Issue Tracker](#)

[Release Notes](#)

[Stack Overflow](#)

**English**

[Terms](#) | [Privacy](#)