## TopoorFlow

TensorFlow API r1.4

## tf.nn.quantized\_max\_pool

```
quantized_max_pool(
    input,
    min_input,
    max_input,
    ksize,
    strides,
    padding,
    name=None
)
```

Defined in tensorflow/python/ops/gen\_nn\_ops.py.

See the guide: Neural Network > Candidate Sampling

Produces the max pool of the input tensor for quantized types.

## Args:

- input: A **Tensor**. Must be one of the following types: **qint8**, **quint8**, **quint16**, **quint16**, **qint32**. The 4D (batch x rows x cols x depth) Tensor to MaxReduce over.
- min\_input: A Tensor of type float32. The float value that the lowest quantized input value represents.
- max\_input: A Tensor of type float32. The float value that the highest quantized input value represents.
- ksize: A list of ints. The size of the window for each dimension of the input tensor. The length must be 4 to match the number of dimensions of the input.
- strides: A list of ints. The stride of the sliding window for each dimension of the input tensor. The length must be 4 to match the number of dimensions of the input.
- padding: A string from: "SAME", "VALID". The type of padding algorithm to use.
- name: A name for the operation (optional).

## Returns:

A tuple of **Tensor** objects (output, min\_output, max\_output).

- output: A Tensor. Has the same type as input.
- min\_output: A Tensor of type float32. The float value that the lowest quantized output value represents.
- max\_output : A Tensor of type float32 . The float value that the highest quantized output value represents.

Except as otherwise noted, the content of this page is licensed under the Creative Commons Attribution 3.0 License, and code samples are licensed under the Apache 2.0 License. For details, see our Site Policies. Java is a registered trademark of Oracle and/or its affiliates.

Last updated November 2, 2017.

GitHub	
Twitter	
Support	
Issue Tracker	
Release Notes	
Stack Overflow	
English	
Terms   Privacy	