#### TopoorFlow

TensorFlow API r1.4

## tf.keras.utils.HDF5Matrix

Contents
Class HDF5Matrix
Properties
dtype
ndim

#### Class **HDF5Matrix**

Defined in tensorflow/python/keras/\_impl/keras/utils/io\_utils.py.

Representation of HDF5 dataset to be used instead of a Numpy array.

#### Example:

```
x_data = HDF5Matrix('input/file.hdf5', 'data')
model.predict(x_data)
```

Providing start and end allows use of a slice of the dataset.

Optionally, a normalizer function (or lambda) can be given. This will be called on every slice of data retrieved.

#### Arguments:

- datapath: string, path to a HDF5 file
- dataset : string, name of the HDF5 dataset in the file specified in datapath
- start: int, start of desired slice of the specified dataset
- end: int, end of desired slice of the specified dataset
- normalizer: function to be called on data when retrieved

#### Returns:

An array-like HDF5 dataset.

# **Properties**

#### dtype

Gets the datatype of the dataset.

Returns:

A numpy dtype string.

### ndim

Gets the number of dimensions (rank) of the dataset.

#### Returns:

An integer denoting the number of dimensions (rank) of the dataset.

### shape

Gets a numpy-style shape tuple giving the dataset dimensions.

Returns:

A numpy-style shape tuple.

#### size

Gets the total dataset size (number of elements).

Returns:

An integer denoting the number of elements in the dataset.

## Methods

## \_\_init\_\_

```
__init__(
   datapath,
   dataset,
   start=0,
   end=None,
   normalizer=None
)
```

## \_\_getitem\_\_

```
__getitem__(key)
```

## \_\_len\_\_

```
__len__()
```

## Class Members

#### refs

Except as otherwise noted, the content of this page is licensed under the Creative Commons Attribution 3.0 License, and code samples are licensed under the Apache 2.0 License. For details, see our Site Policies. Java is a registered trademark of Oracle and/or its affiliates.

Last updated November 2, 2017.

