

tf.floordiv

```
floordiv(  
    x,  
    y,  
    name=None  
)
```

Defined in [tensorflow/python/ops/math_ops.py](#).

See the guide: [Math > Arithmetic Operators](#)

Divides x / y elementwise, rounding toward the most negative integer.

The same as `tf.div(x,y)` for integers, but uses `tf.floor(tf.div(x,y))` for floating point arguments so that the result is always an integer (though possibly an integer represented as floating point). This op is generated by `x // y` floor division in Python 3 and in Python 2.7 with `from __future__ import division`.

Note that for efficiency, `tf.floordiv` uses C semantics for negative numbers (unlike Python and Numpy).

`x` and `y` must have the same type, and the result will have the same type as well.

Args:

- `x`: **Tensor** numerator of real numeric type.
- `y`: **Tensor** denominator of real numeric type.
- `name`: A name for the operation (optional).

Returns:

x / y rounded down (except possibly towards zero for negative integers).

Raises:

- **TypeError**: If the inputs are complex.

Except as otherwise noted, the content of this page is licensed under the [Creative Commons Attribution 3.0 License](#), and code samples are licensed under the [Apache 2.0 License](#). For details, see our [Site Policies](#). Java is a registered trademark of Oracle and/or its affiliates.

Last updated November 2, 2017.

Stay Connected

[Blog](#)

[GitHub](#)

[Twitter](#)

Support

[Issue Tracker](#)

[Release Notes](#)

[Stack Overflow](#)

English

[Terms](#) | [Privacy](#)