TopoorFlow

TensorFlow API r1.4

tf.parse_single_example

```
parse_single_example(
    serialized,
    features,
    name=None,
    example_names=None
)
```

Defined in tensorflow/python/ops/parsing_ops.py.

See the guides: Inputs and Readers > Converting, Reading data > Reading from files

Parses a single **Example** proto.

Similar to parse_example, except:

For dense tensors, the returned **Tensor** is identical to the output of **parse_example**, except there is no batch dimension, the output shape is the same as the shape given in **dense_shape**.

For **SparseTensor** s, the first (batch) column of the indices matrix is removed (the indices matrix is a column vector), the values vector is unchanged, and the first (**batch_size**) entry of the shape vector is removed (it is now a single element vector).

One might see performance advantages by batching **Example** protos with **parse_example** instead of using this function directly.

Args:

- serialized: A scalar string Tensor, a single serialized Example. See _parse_single_example_raw documentation for more details.
- features: A dict mapping feature keys to FixedLenFeature or VarLenFeature values.
- name: A name for this operation (optional).
- example_names: (Optional) A scalar string Tensor, the associated name. See _parse_single_example_raw documentation for more details.

Returns:

A dict mapping feature keys to Tensor and SparseTensor values.

Raises:

ValueError: if any feature is invalid.

Except as otherwise noted, the content of this page is licensed under the Creative Commons Attribution 3.0 License, and code samples are licensed under the Apache 2.0 License. For details, see our Site Policies. Java is a registered trademark of Oracle and/or its affiliates.

Stay Connected	
Blog	
GitHub	
Twitter	
Support	
Issue Tracker	
Release Notes	
Stack Overflow	
English	
Terms Privacy	