

tf.profiler.profile

```
profile(  
    graph,  
    run_meta=None,  
    op_log=None,  
    cmd='scope',  
    options=_DEFAULT_PROFILE_OPTIONS  
)
```

Defined in [tensorflow/python/profiler/model_analyzer.py](#).

Profile model.

Tutorials and examples can be found in:

<https://github.com/tensorflow/tensorflow/tree/master/tensorflow/core/profiler/README.md>

Args:

- `graph`: required tf.Graph.
- `run_meta`: optional tensorflow.RunMetadata proto. It is necessary to support run time information profiling, such as time and memory.
- `op_log`: tensorflow.tfprof.OpLogProto proto. User can assign "types" to graph nodes with op_log. "types" allow user to flexibly group and account profiles using options['accounted_type_regexes'].
- `cmd`: string. Either 'op', 'scope', 'graph' or 'code'. 'op' view organizes profile using operation type. (e.g. MatMul) 'scope' view organizes profile using graph node name scope. 'graph' view organizes profile using graph node inputs/outputs. 'code' view organizes profile using Python call stack.
- `options`: A dict of options. See core/profiler/g3doc/options.md.

Returns:

If cmd is 'scope' or 'graph', returns GraphNodeProto proto. If cmd is 'op' or 'code', returns MultiGraphNodeProto proto. Side effect: stdout/file/timeline.json depending on options['output']

Except as otherwise noted, the content of this page is licensed under the [Creative Commons Attribution 3.0 License](#), and code samples are licensed under the [Apache 2.0 License](#). For details, see our [Site Policies](#). Java is a registered trademark of Oracle and/or its affiliates.

Last updated November 2, 2017.

Stay Connected

Blog

GitHub

Twitter

Support

[Issue Tracker](#)

[Release Notes](#)

[Stack Overflow](#)

English

[Terms](#) | [Privacy](#)