

tf.image.total_variation

```
total_variation(  
    images,  
    name=None  
)
```

Defined in [tensorflow/python/ops/image_ops_impl.py](#).

See the guide: [Images > Denoising](#)

Calculate and return the total variation for one or more images.

The total variation is the sum of the absolute differences for neighboring pixel-values in the input images. This measures how much noise is in the images.

This can be used as a loss-function during optimization so as to suppress noise in images. If you have a batch of images, then you should calculate the scalar loss-value as the sum: `loss = tf.reduce_sum(tf.image.total_variation(images))`

This implements the anisotropic 2-D version of the formula described here:

https://en.wikipedia.org/wiki/Total_variation_denoising

Args:

- `images`: 4-D Tensor of shape `[batch, height, width, channels]` or 3-D Tensor of shape `[height, width, channels]`.
- `name`: A name for the operation (optional).

Raises:

- `ValueError`: if `images.shape` is not a 3-D or 4-D vector.

Returns:

The total variation of `images`.

If `images` was 4-D, return a 1-D float Tensor of shape `[batch]` with the total variation for each image in the batch. If `images` was 3-D, return a scalar float with the total variation for that image.

Except as otherwise noted, the content of this page is licensed under the [Creative Commons Attribution 3.0 License](#), and code samples are licensed under the [Apache 2.0 License](#). For details, see our [Site Policies](#). Java is a registered trademark of Oracle and/or its affiliates.

Last updated November 2, 2017.

Stay Connected

[Blog](#)

[GitHub](#)

[Twitter](#)

Support

[Issue Tracker](#)

[Release Notes](#)

[Stack Overflow](#)

English

[Terms](#) | [Privacy](#)