

tf.errors.InternalError

Contents

Class `InternalError`

Properties

`error_code``message`Class **InternalError**Inherits From: `OpError`Defined in `tensorflow/python/framework/errors_impl.py`.See the guide: [Running Graphs > Error classes and convenience functions](#)

Raised when the system experiences an internal error.

This exception is raised when some invariant expected by the runtime has been broken. Catching this exception is not recommended.

Properties

error_code

The integer error code that describes the error.

message

The error message that describes the error.

node_defThe `NodeDef` proto representing the op that failed.**op**

The operation that failed, if known.

N.B. If the failed op was synthesized at runtime, e.g. a `Send` or `Recv` op, there will be no corresponding `tf.Operation` object. In that case, this will return `None`, and you should instead use the `tf.OpError.node_def` to discover information about the op.

Returns:

The `Operation` that failed, or `None`.

Methods

`__init__`

```
__init__(
    node_def,
    op,
    message
)
```

Creates an `InternalError`.

Except as otherwise noted, the content of this page is licensed under the [Creative Commons Attribution 3.0 License](#), and code samples are licensed under the [Apache 2.0 License](#). For details, see our [Site Policies](#). Java is a registered trademark of Oracle and/or its affiliates.

Last updated November 2, 2017.

Stay Connected

[Blog](#)

[GitHub](#)

[Twitter](#)

Support

[Issue Tracker](#)

[Release Notes](#)

[Stack Overflow](#)

English

[Terms](#) | [Privacy](#)