TensorFlow API r1.4

tf.nn.ctc_greedy_decoder

```
ctc_greedy_decoder(
    inputs,
    sequence_length,
    merge_repeated=True
)
```

Defined in tensorflow/python/ops/ctc_ops.py.

See the guide: Neural Network > Connectionist Temporal Classification (CTC)

Performs greedy decoding on the logits given in input (best path).



★ Note: Regardless of the value of merge_repeated, if the maximum index of a given time and batch corresponds to the blank index (num_classes - 1), no new element is emitted.

If merge_repeated is True, merge repeated classes in output. This means that if consecutive logits' maximum indices are the same, only the first of these is emitted. The sequence A B B * B * B (where '*' is the blank label) becomes

- A B B B if merge_repeated=True.
- A B B B B if merge_repeated=False.

Args:

- inputs: 3-D float Tensor sized [max_time x batch_size x num_classes] . The logits.
- sequence_length: 1-D int32 vector containing sequence lengths, having size [batch_size] .
- merge_repeated: Boolean. Default: True.

Returns:

A tuple (decoded, neg_sum_logits) where decoded: A single-element list. decoded[0] is an SparseTensor containing the decoded outputs s.t.:

```
decoded.indices: Indices matrix (total_decoded_outputs x 2). The rows store: [batch, time].
```

decoded.values: Values vector, size (total_decoded_outputs). The vector stores the decoded classes.

decoded.shape: Shape vector, size (2). The shape values are: [batch_size, max_decoded_length] neg_sum_logits: A float matrix (batch_size x 1) containing, for the sequence found, the negative of the sum of the greatest logit at each timeframe.

Except as otherwise noted, the content of this page is licensed under the Creative Commons Attribution 3.0 License, and code samples are licensed under the Apache 2.0 License. For details, see our Site Policies. Java is a registered trademark of Oracle and/or its affiliates.

Last updated November 2, 2017.

łub	
iter	
port	
e Tracker	
ease Notes	
ck Overflow	
glish	
ns Privacy	