TancarFlow

TensorFlow API r1.4

Module: tf.contrib.distributions.bijectors

Contents Classes

Defined in tensorflow/contrib/distributions/python/ops/bijectors/__init__.py.

Bijector Ops.

Classes

```
class AbsoluteValue: Computes Y = g(X) = Abs(X), element-wise.
class Affine: Compute Y = g(X; shift, scale) = scale @ X + shift.
class AffineLinearOperator: Compute Y = g(X; shift, scale) = scale @ X + shift.
class Bijector: Interface for transformations of a Distribution sample.
class Chain: Bijector which applies a sequence of bijectors.
class CholeskyOuterProduct: Compute g(X) = X @ X.T; X is lower-triangular, positive-diagonal matrix.
class ConditionalBijector: Conditional Bijector is a Bijector that allows intrinsic conditioning.
class Exp: Compute Y = g(X) = exp(X).
class Identity: Compute Y = g(X) = X.
class Inline: Bijector constructed from custom callables.
class Invert: Bijector which inverts another Bijector.
class PowerTransform: Compute Y = g(X) = (1 + X * c) * *(1 / c), X >= -1 / c.
class Sigmoid: Bijector which computes Y = g(X) = 1 / (1 + exp(-X)).
class SigmoidCentered: Bijector which computes Y = g(X) = exp([X \ 0]) / (1 + exp(-X)).
class SinhArcsinh: Compute Y = g(X) = Sinh((Arcsinh(X) + skewness) * tailweight).
class SoftmaxCentered: Bijector which computes Y = g(X) = \exp([X \ \theta]) / \sup(\exp([X \ \theta])).
class Softplus: Bijector which computes Y = g(X) = Log[1 + exp(X)].
```

Except as otherwise noted, the content of this page is licensed under the Creative Commons Attribution 3.0 License, and code samples are licensed under the Apache 2.0 License. For details, see our Site Policies. Java is a registered trademark of Oracle and/or its affiliates.

Last updated November 2, 2017.

Blog			
GitHub			
Twitter			
Support			
oupport			
Issue Tracker			
Release Notes			
Stack Overflow			
English			
Terms Privacy			