

tf.train.SessionRunValues

Contents

Class `SessionRunValues`

Properties

`options`

`results`

`run_metadata`

Methods

`__new__`

Class `SessionRunValues`

Defined in [tensorflow/python/training/session_run_hook.py](#).

See the guide: [Training > Training Hooks](#)

Contains the results of `Session.run()`.

In the future we may use this object to add more information about result of run without changing the Hook API.

Args:

- `results`: The return values from `Session.run()` corresponding to the fetches attribute returned in the RunArgs. Note that this has the same shape as the RunArgs fetches. For example: `fetches = global_step_tensor => results = nparray(int)` `fetches = [train_op, summary_op, global_step_tensor] => results = [None, nparray(string), nparray(int)]` `fetches = {'step': global_step_tensor, 'summ': summary_op} => results = {'step': nparray(int), 'summ': nparray(string)}`
- `options`: `RunOptions` from the `Session.run()` call.
- `run_metadata`: `RunMetadata` from the `Session.run()` call.

Properties

`options`

Alias for field number 1

`results`

Alias for field number 0

`run_metadata`

Alias for field number 2

Methods

__new__

```
__new__(
    _cls,
    results,
    options,
    run_metadata
)
```

Create new instance of SessionRunValues(results, options, run_metadata)

Except as otherwise noted, the content of this page is licensed under the [Creative Commons Attribution 3.0 License](#), and code samples are licensed under the [Apache 2.0 License](#). For details, see our [Site Policies](#). Java is a registered trademark of Oracle and/or its affiliates.

Last updated November 2, 2017.

Stay Connected

[Blog](#)

[GitHub](#)

[Twitter](#)

Support

[Issue Tracker](#)

[Release Notes](#)

[Stack Overflow](#)

English

[Terms](#) | [Privacy](#)