

## tf.keras.preprocessing.image.random\_shear

```
random_shear(  
    x,  
    intensity,  
    row_axis=1,  
    col_axis=2,  
    channel_axis=0,  
    fill_mode='nearest',  
    cval=0.0  
)
```

Defined in [tensorflow/python/keras/\\_impl/keras/preprocessing/image.py](#).

Performs a random spatial shear of a Numpy image tensor.

## Arguments:

- `x`: Input tensor. Must be 3D.
- `intensity`: Transformation intensity.
- `row_axis`: Index of axis for rows in the input tensor.
- `col_axis`: Index of axis for columns in the input tensor.
- `channel_axis`: Index of axis for channels in the input tensor.
- `fill_mode`: Points outside the boundaries of the input are filled according to the given mode (one of `{'constant', 'nearest', 'reflect', 'wrap'}`).
- `cval`: Value used for points outside the boundaries of the input if `mode='constant'`.

## Returns:

Sheared Numpy image tensor.

---

Except as otherwise noted, the content of this page is licensed under the [Creative Commons Attribution 3.0 License](#), and code samples are licensed under the [Apache 2.0 License](#). For details, see our [Site Policies](#). Java is a registered trademark of Oracle and/or its affiliates.

Last updated November 2, 2017.

## Stay Connected

[Blog](#)

[GitHub](#)

[Twitter](#)

## Support

[Issue Tracker](#)

[Release Notes](#)

[Stack Overflow](#)

**English**

[Terms](#) | [Privacy](#)