### TencorFlow

TensorFlow API r1.4

tf.layers.max\_pooling2d

```
max_pooling2d(
   inputs,
   pool_size,
   strides,
   padding='valid',
   data_format='channels_last',
   name=None
)
```

Defined in tensorflow/python/layers/pooling.py.

Max pooling layer for 2D inputs (e.g. images).

# Arguments:

- inputs: The tensor over which to pool. Must have rank 4.
- pool\_size: An integer or tuple/list of 2 integers: (pool\_height, pool\_width) specifying the size of the pooling window. Can be a single integer to specify the same value for all spatial dimensions.
- strides: An integer or tuple/list of 2 integers, specifying the strides of the pooling operation. Can be a single integer to specify the same value for all spatial dimensions.
- padding: A string. The padding method, either 'valid' or 'same'. Case-insensitive.
- data\_format: A string. The ordering of the dimensions in the inputs. channels\_last (default) and channels\_first are supported. channels\_last corresponds to inputs with shape (batch, height, width, channels) while channels\_first corresponds to inputs with shape (batch, channels, height, width).
- name: A string, the name of the layer.

## Returns:

Output tensor.

Except as otherwise noted, the content of this page is licensed under the Creative Commons Attribution 3.0 License, and code samples are licensed under the Apache 2.0 License. For details, see our Site Policies. Java is a registered trademark of Oracle and/or its affiliates.

Last updated November 2, 2017.

# Stay Connected Blog GitHub Twitter

# Support

Issue Tracker
Release Notes
Stack Overflow

English
Terms | Privacy