

tf.ones_like

```
ones_like(  
    tensor,  
    dtype=None,  
    name=None,  
    optimize=True  
)
```

Defined in [tensorflow/python/ops/array_ops.py](#).

See the guide: [Constants, Sequences, and Random Values > Constant Value Tensors](#)

Creates a tensor with all elements set to 1.

Given a single tensor (**tensor**), this operation returns a tensor of the same type and shape as **tensor** with all elements set to 1. Optionally, you can specify a new type (**dtype**) for the returned tensor.

For example:

```
tensor = tf.constant([[1, 2, 3], [4, 5, 6]])  
tf.ones_like(tensor) # [[1, 1, 1], [1, 1, 1]]
```

Args:

- **tensor**: A **Tensor**.
- **dtype**: A type for the returned **Tensor**. Must be **float32**, **float64**, **int8**, **int16**, **int32**, **int64**, **uint8**, **complex64**, **complex128** or **bool**.
- **name**: A name for the operation (optional).
- **optimize**: if true, attempt to statically determine the shape of 'tensor' and encode it as a constant.

Returns:

A **Tensor** with all elements set to 1.

Except as otherwise noted, the content of this page is licensed under the [Creative Commons Attribution 3.0 License](#), and code samples are licensed under the [Apache 2.0 License](#). For details, see our [Site Policies](#). Java is a registered trademark of Oracle and/or its affiliates.

Last updated November 2, 2017.

Stay Connected

[Blog](#)

[GitHub](#)

[Twitter](#)

Support

[Issue Tracker](#)

[Release Notes](#)

[Stack Overflow](#)

English

[Terms](#) | [Privacy](#)