

## tf.losses.get\_total\_loss

```
get_total_loss(  
    add_regularization_losses=True,  
    name='total_loss'  
)
```

Defined in [tensorflow/python/ops/losses/util.py](#).

Returns a tensor whose value represents the total loss.

In particular, this adds any losses you have added with `tf.add_loss()` to any regularization losses that have been added by regularization parameters on layers constructors e.g. `tf.layers`. Be very sure to use this if you are constructing a `loss_op` manually. Otherwise regularization arguments on `tf.layers` methods will not function.

### Args:

- `add_regularization_losses`: A boolean indicating whether or not to use the regularization losses in the sum.
- `name`: The name of the returned tensor.

### Returns:

A `Tensor` whose value represents the total loss.

### Raises:

- `ValueError`: if `losses` is not iterable.

---

Except as otherwise noted, the content of this page is licensed under the [Creative Commons Attribution 3.0 License](#), and code samples are licensed under the [Apache 2.0 License](#). For details, see our [Site Policies](#). Java is a registered trademark of Oracle and/or its affiliates.

Last updated November 2, 2017.

### Stay Connected

[Blog](#)

[GitHub](#)

[Twitter](#)

### Support

[Issue Tracker](#)

[Release Notes](#)

[Stack Overflow](#)

