

tf.unsorted_segment_sum

```

unsorted_segment_sum(
    data,
    segment_ids,
    num_segments,
    name=None
)

```

Defined in `tensorflow/python/ops/gen_math_ops.py`.

See the guide: [Math > Segmentation](#)


Computes the sum along segments of a tensor.

Read [the section on segmentation](#) for an explanation of segments.

Computes a tensor such that $(\text{output}[i] = \sum_{j \dots} \text{data}[j \dots])$ where the sum is over tuples $j \dots$ such that $\text{segment_ids}[j \dots] == i$. Unlike `SegmentSum`, `segment_ids` need not be sorted and need not cover all values in the full range of valid values.

If the sum is empty for a given segment ID i , $\text{output}[i] = 0$.

`num_segments` should equal the number of distinct segment IDs.



Args:

- `data`: A **Tensor**. Must be one of the following types: `float32`, `float64`, `int64`, `int32`, `uint8`, `uint16`, `int16`, `int8`, `complex64`, `complex128`, `qint8`, `quint8`, `qint32`, `half`.
- `segment_ids`: A **Tensor**. Must be one of the following types: `int32`, `int64`. A tensor whose shape is a prefix of `data.shape`.
- `num_segments`: A **Tensor** of type `int32`.
- `name`: A name for the operation (optional).

Returns:

A **Tensor**. Has the same type as `data`. Has same shape as data, except for the first `segment_ids.rank` dimensions, which are replaced with a single dimension which has size `num_segments`.

Except as otherwise noted, the content of this page is licensed under the [Creative Commons Attribution 3.0 License](#), and code samples are licensed under the [Apache 2.0 License](#). For details, see our [Site Policies](#). Java is a registered trademark of Oracle and/or its affiliates.

Last updated November 2, 2017.

Stay Connected

[Blog](#)

[GitHub](#)

[Twitter](#)

Support

[Issue Tracker](#)

[Release Notes](#)

[Stack Overflow](#)

English

[Terms](#) | [Privacy](#)